Factory default and user-adjustable settings (4303102)

Working mode	MANUAL (user-adjustable via APP)
Set point	55°C (user-adjustable via APP)
Maximum set point	70°C
Minimum set point	20°C
Hysteresis	12°C
Mechanical safety threshold	110°C +8°C/-5°C
ECO first week set point	70°C
ECO following weeks maximum set point	60°C
ECO following weeks minimum set point	40°C
PROGRAMMING (AUTO) set point	55°C (user-adjustable via APP)
PROGRAMMING (AUTO) COMFORT set point	20°C (user-adjustable via APP)
PROGRAMMING (AUTO) period	24/7 @ set point (user-adjustable via APP)
PROGRAMMING (AUTO) PRE-HEATING	Disabled (user-adjustable via APP)
HOLIDAY maximum period	49 days
Boost set point	70°C (user-adjustable via APP)
Boost maximum set point	Maximum set point
Boost minimum set point	20°C
Boost duration	180 minutes (user-adjustable via APP)
Boost maximum duration	300 minutes
Boost minimum duration	30 minutes
Antibacterial set point	70°C
Antibacterial threshold	62°C
Antibacterial period	30 minutes
Antibacterial intervals	2 hours (first connection) | 30 days
Antifreeze set point	5°C + Hysteresis
Water heater power	- Watt (user-adjustable via APP)
Electricity average price per kWh	- (user-adjustable via APP)

This document is the property of Thermowatt S.p.A and, as a result of continuous product improvements, these specifications are subject to change without prior notice.
No part of this document may be even partially circulated, quoted, reproduced or disclosed to third parties without prior written approval from Thermowatt S.p.A.